

Technical data sheet for

## P10M PROVER/HOLDING CABINET

1/1 GN 10 Tray Manual / Electric



P10M

Unit shall be a Moffat electrically heated Turbofan Prover and Holding Cabinet. The prover and holding cabinet shall have double skin construction with stainless steel interior and exterior sides, front and top. Door shall be side hinged and field reversible. Unit shall have capacity for up to 10 1/1 GN Gastronorm pans. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinet shall be controlled by a mechanical thermostat and humidity via a control of the water tank. A thermometer shall indicate the cabinet temperature. Prover and holding cabinet shall be mounted on castors, with two rigid castors at rear and two swivel castors dual swivel and wheel lock and front. Prover and Holding cabinet shall operate independently or in combination with Moffat Turbofan model E33D5 Convection Oven. Prover and Holding Cabinets shall be fitted with 10A cordsets. Unit shall be supplied in 100% recyclable shipping packaging.

### STANDARD FEATURES

- Dual function Prover and Holding Cabinet
- Designed for individual use or system installed with Turbofan E33D Convection Oven
- 10 1/1 GN Gastronorm pan capacity
- 74mm tray spacing
- Compact 610mm width
- 10A plug-in cordset fitted
- Full double skin construction
- Auto water fill system with optional integrated water filter kit
- Continuous door seal
- Off / Prove / Hold mode selection
- Low velocity circulation fan system
- Mechanical thermostat
- Humidity level control
- Dual halogen cabinet interior lamps
- Cabinet temperature display thermometer
- 4 dia. 76mm castors with 2 front castors dual wheel and swivel lock, 2 rigid rear castors
- 100% recyclable packaging

### ACCESSORIES

- Optional 3M Cuno water filter kit complete with cartridge and connection fittings

### P10M 1/1 GN Manual / Electric Prover/Holding Cabinet

#### CONSTRUCTION

304 stainless steel interior cabinet  
 Stainless steel front, sides and top exterior  
 Stainless steel interior side racks  
 Stainless steel frame side hinged door  
 5mm thick door glass  
 Stainless steel control panel  
 Aluminized coated steel base and rear panels

#### CONTROLS

Off / Prove / Holding mode selector switch.  
 Mechanical thermostat 20-85°C  
 Air heating ON control panel indicator  
 Humidity level control  
 Humidity tank ON control panel indicator  
 Cabinet temperature thermometer  
 Auto-fill water system standard

#### CLEANING

Stainless steel top and side exterior panels  
 Stainless steel interior chamber  
 Easy access to all interior surfaces  
 Fully removable stainless steel rack support  
 Removable humidity water tank (no tools)

#### SPECIFICATIONS

Electrical Requirements  
 230-240V, 50Hz, 1P+N+E, 1.5kW, 6.3A  
 10A cordset fitted

#### Water Requirements (optional)

Cold water connection 3/4" BSP male  
 80psi maximum inlet pressure / 20psi minimum inlet pressure

#### External Dimensions

Width 610mm  
 Height 1015mm including dia. 76mm castors  
 Depth 680mm

#### Nett Weight

77.5kg

#### Packing Data

95.3kg  
 0.64m<sup>3</sup>  
 Width 655mm  
 Height 1180mm  
 Depth 830mm

#### INSTALLATION CLEARANCES

Rear 25mm  
 LH Side 0mm  
 RH Side 0mm

#### CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is required



Australia  
[www.moffat.com.au](http://www.moffat.com.au)  
 New Zealand  
[www.moffat.co.nz](http://www.moffat.co.nz)  
[www.turbofanoven.com](http://www.turbofanoven.com)

Australia  
 Moffat Pty Limited

Victoria/Tasmania  
 740 Springvale Road  
 Mulgrave, Victoria 3170  
 Telephone 03-9518 3888  
 Facsimile 03-9518 3833  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

New South Wales  
 Telephone 02-8833 4111  
[nswsales@moffat.com.au](mailto:nswsales@moffat.com.au)

South Australia  
 Telephone 03-9518 3888  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

Queensland  
 Telephone 07-3630 8600  
[qldsales@moffat.com.au](mailto:qldsales@moffat.com.au)

Western Australia  
 Telephone 08-9202 6820  
[bgarcia@moffat.com.au](mailto:bgarcia@moffat.com.au)

New Zealand  
 Moffat Limited

Christchurch  
 45 Illinois Drive  
 Izone Business Hub  
 Rolleston 7675  
 Telephone +64 3-983 6600  
 Facsimile +64 3-983 6660  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)

Auckland  
 Telephone 09-574 3150  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)



Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

